

RA Family, RX Family, RL78 Family, RZ Family

HS400x Sample Software Manual

Introduction

This application note describes the sample software that is for use with the HS400x humidity and temperature sensor and runs on certain MCUs of the RA family, RX family, RL78 family, and RZ family.

Target Devices

RA6M4 Group

RA0E1 Group

RX65N Group

RL78/G14 Group

RL78/G23 Group

RZ/G2L Group

Trademarks

FreeRTOS™ and FreeRTOS.org™ are trade marks of Amazon Web Services, Inc.

Microsoft® Azure RTOS is a trademark of the Microsoft group of companies.

All other trademarks are property of their respective owners.

Contents

1. Overview	4
2. Environment for Confirming Operation.....	4
2.1 Environment for Confirming Operation on the RA6M4 Group MCU	4
2.2 Environment for Confirming Operation on the RA0E1 Group MCU	6
2.3 Environment for Confirming Operation on the RX Family MCU	7
2.4 Environment for Confirming Operation on the RL78/G14 Group MCU	8
2.5 Environment for Confirming Operation on the RL78/G23 Group MCU	9
2.6 Environment for Confirming Operation on the RZ Family MCU	10
3. Sensor Specifications	11
3.1 Overview of Sensor Specifications	11
3.2 Sensor Functions.....	11
3.2.1 I2C Communication Interface.....	12
3.2.2 Expressions for Converting Output Values to Humidity and Temperature	12
4. Specifications of Sample Software.....	13

4.1	Configuration of the Sample Software.....	13
4.2	Specifications of Sensor API Functions	13
4.2.1	List of Sensor API Functions	13
4.2.2	Guide to Using the API Functions	14
4.3	Flowchart of the Main Processing in the Non-OS Version of the Sample Software	16
4.4	Flowchart of the OS Version of the Sample Software	18
4.5	Azure RTOS Project.....	20
5.	Configuration Settings	21
5.1	HS400x Humidity and Temperature Sensor Settings	21
5.1.1	RA Family	21
5.1.2	RX Family	22
5.1.3	RL78 Family	23
5.1.4	RZ Family	25
5.2	Sensor Communication Middleware Settings	26
5.2.1	RA Family	26
5.2.2	RX Family	27
5.2.3	RL78 Family	28
5.2.4	RZ Family	29
5.3	I2C Driver Settings	30
5.3.1	RA Family	30
5.3.2	RX Family	36
5.3.3	RL78 Family	42
5.3.4	RZ Family	44
6.	Guide to Changing the Target Device.....	46
6.1	RA Sample Project	46
6.1.1	Importing the Sample Project.....	46
6.1.2	Modifying Settings of the FSP Configurator	48
6.1.2.1	[BSP] Setting	48
6.1.2.2	[Clocks] Setting	48
6.1.2.3	[Pins] Setting	49
6.1.2.4	[Stacks] Setting	52
(1)	I2C Driver	52
(a)	When using the same I2C driver as the original sample project	52
(b)	When using the different I2C driver as the original sample project	53
(2)	I/O Port	54
(3)	Others.....	54
6.1.3	Changing the Toolchain Setting	54
6.2	RX Sample Project	55
6.2.1	Importing the Sample Project.....	55

6.2.2	Changing the Device	57
6.2.3	Modifying Settings of the Smart Configurator	59
6.2.4	Changing the Toolchain Setting	61
6.3	RL78 Sample Project.....	62
6.3.1	Creating a New Project	62
6.3.2	Settings of the Code Generator.....	64
6.3.3	Modifying the Generated Code	68
6.3.4	Modifying Sample Source Files.....	72
6.4	RZ Sample Project	77
6.4.1	Importing the Sample Project.....	77
6.4.2	Modifying Settings of the FSP Configurator	79
6.4.1	Changing sample code.....	81
7.	Viewing Temperature and Humidity Data.....	82
	Revision History	84
	General Precautions in the Handling of Microprocessing Unit and Microcontroller Unit Products..	85
	Notice	86
	Corporate Headquarters	86
	Contact information.....	86
	Trademarks.....	86

1. Overview

This sample software acquires humidity and temperature data from the HS400x humidity and temperature sensor and handles calculations on the data. In combination with the I2C driver of the FSP or FIT, the sample software controls the HS400x through the I2C in the MCU to measure humidity and temperature, acquire ADC data, and calculate the acquired data.

2. Environment for Confirming Operation

2.1 Environment for Confirming Operation on the RA6M4 Group MCU

The operation of this software has been confirmed on the MCU of the RA6M4 group in the following environment.

Table 2-1 Operating Environment for the RA6M4 Group MCU

Item	Description
Demonstration board	RTK7EKA6M4S00001BE (EK-RA6M4)
Microcontroller	RA6M4 (R7FA6M4AF3CFB: 144 pins)
Operating frequency	200 MHz
Operating voltage	5 V
Integrated development environment	e ² Studio 2023-01
C compiler	GCC 10.3.1.20210824 IAR ANSI C/C++ Compiler V8.50.9.278/LNX for ARM ARM Compiler 6.16
FSP	V.3.8.0
RTOS	FreeRTOS™ or Microsoft® Azure RTOS
Emulator	On-board debugger (J-LINK)
Interposer	Interposer board to convert Type2/3 to Type 6A PMOD standard (US082-INTERPEVZ)
Sensor board	Relative humidity sensor Pmod™ board (US082-HS4001EVZ)

Table 2-2 Amount of Memory Used in the RA6M4 Group MCU

Area	Size
ROM	Non-OS version: 1,785 bytes FreeRTOS version: 2,158 bytes Azure RTOS version: 2,130 bytes
RAM	Non-OS version: 101 bytes FreeRTOS version: 281 bytes Azure RTOS version: 450 bytes

Calculation of these sizes in memory only takes functions and variables related to the HS400x sensor into account. They do not include the sizes of RTOS threads for the RTOS versions.




Figure 2-1 Hardware Connections for the RA6M4 Group

2.2 Environment for Confirming Operation on the RA0E1 Group MCU

The operation of this software has been confirmed on the MCU of the RA0E1 group in the following environment.

Table 2-3 Operating Environment for the RA0E1 Group MCU

Item	Description
Demonstration board	RTK7FPA0E1S00W2BJ (RA0E1 Fast Prototyping Board)
Microcontroller	RA0E1 (R7FA0E1073CFJ:32pin)
Operating frequency	32 MHz
Operating voltage	5 V
Integrated development environment	e ² Studio 2024-01.1
C compiler	GNU ARM Embedded 13.2.1.arm-13-7
FSP	V.5.2.0
RTOS	FreeRTOS™
Emulator	On-board debugger (J-LINK)
Sensor board	Relative humidity sensor Pmod™ board (US082-HS4001EVZ)

Table 2-4 Amount of Memory Used in the RA0E1 Group MCU

Area	Size
ROM	Non-OS version: 1,280 bytes FreeRTOS version: 1,414 bytes
RAM	Non-OS version: 86 bytes FreeRTOS version: 164 bytes

Calculation of these sizes in memory only takes functions and variables related to the HS400x sensor into account. They do not include the sizes of RTOS threads for the RTOS versions.




Figure 2-2 Hardware Connections for the RA0E1 Group

2.3 Environment for Confirming Operation on the RX Family MCU

The operation of this software has been confirmed on the MCU of the RX family in the following environment.

Table 2-5 Operating Environment for the RX Family MCU

Item	Description
Demonstration board	RPBRX65N (Envision Kit RX65N)
Microcontroller	RX65N (R5F565NEDDFB: 144 pins)
Operating frequency	12 MHz
Operating voltage	5 V
Integrated development environment	e ² Studio 2023-01 IAR EW for RX 4.20.1
C compiler	Renesas Electronics C/C++ compiler for RX family V.3.03.00 GCC 8.3.0.202004 IAR Toolchain for RX 8.4.10.7051
FIT	BSP V.7.20
RTOS	FreeRTOS™ / Microsoft® Azure RTOS
Emulator	On-board debugger (E2OB)
Interposer	Interposer board to convert Type2/3 to Type 6A PMOD standard (US082-INTERPEVZ)
Sensor board	Relative humidity sensor Pmod™ board (US082-HS4001EVZ)

Table 2-6 Amount of Memory Used in the RX Family MCU

Area	Size
ROM	Non-OS version: 2,075 bytes FreeRTOS version: 2,300 bytes Azure RTOS version: 2,360 bytes
RAM	Non-OS version: 177 bytes FreeRTOS version: 237 bytes Azure RTOS version: 446 bytes

Calculation of these sizes in memory only takes functions and variables related to the HS400x sensor into account. They do not include the sizes of RTOS threads for the RTOS versions.




Figure 2-3 Hardware Connections for the RX Family

2.4 Environment for Confirming Operation on the RL78/G14 Group MCU

The operation of this software has been confirmed on the MCU of the RL78/G14 group in the following environment.

Table 2-7 Operating Environment for the RL78/G14 Group MCU

Item	Description
Demonstration board	RTK5RLG140C00000BJ (RL78/G14 Fast Prototyping Board)
Microcontroller	RL78/G14 (R5F104MLAFB: 80 pins)
Operating frequency	32 MHz
Operating voltage	3.3 V
Integrated development environment	e ² studio 2023-01 IAR EW for RL78 4.21.1
C compiler	C compiler package for RL78 family V1.11.00 GCC for Renesas RL78 4.9.2.202103 IAR Toolchain for RL78 4.21.1.2409
Emulator	On-board debugger (E2OB)
Sensor board	Relative humidity sensor Pmod™ board (US082-HS4001EVZ)

Table 2-8 Amount of Memory Used in the RL78/G14 Group MCU

Area	Size
ROM	1,992 bytes
RAM	118 bytes




Figure 2-4 Hardware Connections for the RL78/G14 Group

2.5 Environment for Confirming Operation on the RL78/G23 Group MCU

The operation of this software has been confirmed on the MCU of the RL78/G23 group in the following environment.

Table 2-9 Operating Environment for the RL78/G23 Group MCU

Item	Description
Demonstration board	RTK7RLG230CSN000BJ (RL78/G23-128p Fast Prototyping Board)
Microcontroller	RL78/G23 (R7F100GSN2DFB: 128 pins)
Operating frequency	32 MHz
Operating voltage	3.3 V
Integrated development environment	e ² studio 2023-01 IAR EW for RL78 4.21.1
C compiler	C compiler package for RL78 family V1.11.00 LLVM for RL78 10.0.0.202209 IAR Toolchain for RL78 4.21.1.2409
Emulator	E2 Lite
Sensor board	Relative humidity sensor Pmod™ board (US082-HS4001EVZ)

Table 2-10 Amount of Memory Used in the RL78/G23 Group MCU

Area	Size
ROM	2,361 bytes
RAM	118 bytes




Figure 2-5 Hardware Connections for the RL78/G23 Group

2.6 Environment for Confirming Operation on the RZ Family MCU

The operation of this software has been confirmed on the MCU of the RZ family in the following environment.

Table 2-11 Operating Environment for the RZ Family MCU

Item	Description
Demonstration board	RTK9744L23S01000BE (RZ/G2L Evaluation Kit (SMARC))
Microcontroller	RZ/G2L (R9A07G044L23GBG :456pin)
Operating frequency	Arm® Cortex®-M33 : 200MHz、 Arm® Cortex®-A55 : 1.2GHz
Operating voltage	5 V
Integrated development environment	e ² Studio 2023-01
C compiler	GCC 10.3.1.20210824
FSP	V.1.2.0
RTOS	FreeRTOS™
Emulator	SEGGER J-LINK BASE
Sensor board	Relative Humidity Sensor Pmod™ Board (QCIOT-HS4001POCZ)

Table 2-12 Amount of Memory Used in the RZ Family MCU

Area	Size
ROM	Non-OS version: 2,060 bytes FreeRTOS version: 2,460 bytes
RAM	Non-OS version: 169 bytes FreeRTOS version: 449 bytes

Calculation of these sizes in memory only takes functions and variables related to the HS400x sensor into account. They do not include the sizes of RTOS threads for the RTOS versions.




Figure 2-6 Hardware Connections for the RZ Family

3. Sensor Specifications

3.1 Overview of Sensor Specifications

Table 3-1 gives an overview of the specifications of the HS400x humidity and temperature sensor.

Table 3-1 Overview of Sensor Specifications

Item	Description
Humidity range	0%RH to 100%RH
Humidity accuracy	±1.5%RH (typ.) (HS4001: 10%RH to 90%RH, 25°C)
Humidity resolution	0.04%RH (typ.)
Hysteresis	±1.0%RH (max.)
Humidity response time	4 seconds (typ.) (in a sealed space)
Temperature range	−40°C to +125°C
Temperature accuracy	±0.2°C (typ.) (HS4001 and HS4002: −10°C to 80°C)
Temperature resolution	0.01°C (typ.)
Temperature response time	2 seconds (typ.) (in a sealed space)
Long-term stability	0.03°C/Yr (max.)
Supply voltage dependency	0.03°C/V (typ.)

3.2 Sensor Functions

This software supports the following functions of HS400x.

Table 3-2 List of Sensor Functions

Function	Description
I2C communications	Sensor data are transferred through I2C communications.
Measurement mode	This software operates with the sensor in sleep mode most of the time. On completion of measurement triggered by a measurement request, the sensor enters sleep mode.
Measurement request	The sensor in sleep mode is placed in the measurement state upon receiving a measurement request.
Data fetch	At the end of a measurement cycle, valid data can be acquired.
Status bits	The status bits for the results of measurement indicate whether the current data are valid or old.

3.2.1 I2C Communication Interface

The following shows the format of measurement data transferred through I2C communications.




Figure 3-1 Format of I2C Communications

3.2.2 Expressions for Converting Output Values to Humidity and Temperature

The HS400x software uses functions for converting the acquired ADC data to values for humidity and temperature. The following shows the conversion expressions.

- Humidity conversion expression

$$Humidity [\%RH] = \left(\frac{Humidity [13:0]}{2^{14} - 1} \right) * 100$$

- Temperature conversion expression

$$Temperature [^{\circ}C] = \left(\frac{Temperature [13:0]}{2^{14} - 1} \right) * 165 - 40$$

4. Specifications of Sample Software

This section describes the specifications of the sample software.

For the FreeRTOS settings for the RX family, refer to the [FAQ](#).

4.1 Configuration of the Sample Software

Figure 4-1 shows the configuration of sample software blocks.




Figure 4-1 Block Diagram of the Sample Software

4.2 Specifications of Sensor API Functions

4.2.1 List of Sensor API Functions

The following table lists the sensor API functions. For details of the API functions, refer to the separately provided RX Family HS400x Sensor API FIT Module application note (R01AN5893) and RL78 Family Renesas Sensor Control Modules application note (R01AN5896).

Table 4-1 List of Sensor API Functions

Function	Description
RM_HS400X_Open	Starts control of the sensor.
RM_HS400X_Close	Terminates control of the sensor.
RM_HS400X_MeasurementStart	Starts measurement by the sensor.
RM_HS400X_MeasurementStop	Stops measurement by the sensor.
RM_HS400X_Read	Acquires raw data from the sensor.
RM_HS400X_DataCalculate	Calculates values from the raw data acquired from the sensor.

4.2.2 Guide to Using the API Functions

The following diagram of API function transitions shows the conditions on the usage of the individual HS400x API functions and the expected orders of function calls.




Figure 4-2 Transitions between API Function Calls

The conditions for calling the individual functions are shown below.

- RM_HS400X_Open: (1) Starting the HS400x or
(12) Restarting after a call of RM_HS400X_Close
- RM_HS400X_Close: (11) Successful completion or abnormal end of individual processing
- RM_HS400X_MeasurementStart: (2) Starting measurement after a call of RM_HS400X_Open,
(5) (7) reading the next measured data, or
(8) retry after waiting for the response to the measurement start request
- RM_HS400X_MeasurementStop: (10) Stop measurement
- RM_HS400X_Read: (3) Reading measured data after a call of
RM_HS400X_MeasurementStart or
(9) retry after waiting for the response to the data acquisition request
- RM_HS400X_DataCalculate: (4) Calculating humidity and temperature data after a call of
RM_HS400X_Read

Notes:

Since RM_HS400X_Open checks the state of the I2C driver, the I2C driver must be opened before the RM_HS400X_Open processing.

Regarding how to open the I2C driver of the RA family and RX family, refer to the `g_comms_i2c_bus0_quick_setup()` function in the sample software. This is not necessary in the RL78 family devices because the I2C driver will be opened in the startup processing.

When measurement is started by RM_HS400X_MeasurementStart, the sensor stops measurement after having updated the ADC data. Therefore, be sure to call RM_HS400X_MeasurementStart at least once every time before executing processing by RM_HS400X_Read.

When using these API functions in an RTOS system, the user will need to control the bus by using a semaphore if the sensor is controlled in multiple threads or tasks at the same time. For the timing of the semaphore being raised and the control of blocking, refer to section 4.4, Flowchart of the OS Version of the Sample Software.

4.3 Flowchart of the Main Processing in the Non-OS Version of the Sample Software

This sample software first opens the driver and then repeats the process of starting the measurement by the sensor, acquiring data from the sensor, and calculating values from the results of measurement.




Figure 4-3 Flowchart 1 of the Main Processing in the Non-OS Version of the Sample Software




Figure 4-4 Flowchart 2 of the Main Processing in the Non-OS Version of the Sample Software

4.4 Flowchart of the OS Version of the Sample Software

The OS version uses a semaphore in control of the sensor and operates one thread for controlling the sensor.

The control of the sensor in the thread first starts the driver and then repeats the process of starting the measurement by the sensor, acquiring data from the sensor, and calculating values from the results of measurement.




Figure 4-5 Flowchart 1 of the Main Processing in the OS Version of the Sample Software




Figure 4-6 Flowchart 2 of the Main Processing in the OS Version of the Sample Software

4.5 Azure RTOS Project

The RX project for use with the Azure RTOS has the following changes from the default source files generated by the RX Smart Configurator.

1. src/demo_thread.c
 - Line 57: Addition of extern void tx_application_define_user (void);
 - Line 178: Addition of tx_application_define_user();
2. libs/threadx/common/inc/tx_api.h
 - Line 224: Change of TX_TIMER_TICKS_PER_SECOND ((ULONG) 1000)

5. Configuration Settings

5.1 HS400x Humidity and Temperature Sensor Settings

5.1.1 RA Family

Select the `rm_hs400x` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-1 HS400x Settings for the RA Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Measurement Type	Hold Measurement	Specify the type of measurement. Select from among "Hold Measurement" (one-shot measurement), "No-Hold Measurement", or "Periodic Measurement" (sequential measurement).
	No-Hold Measurement	
	Periodic Measurement	
Data type	Both humidity and temperature	Specify the type of data to be acquired from the sensor. Both the humidity and temperature or the humidity alone can be selected.
	Humidity only	
Module <code>g_hs400x_sensor</code> HS400X on <code>rm_hs400x</code>		
Name	<code>g_hs400x_sensor0</code>	Specify the name of the module. A module name conforming to the C language standard can be specified.
Temperature Resolution	8-bit	Specify the resolution of temperature measurement.
	10-bit	
	12-bit	
	14-bit	
Humidity Resolution	8-bit	Specify the resolution of humidity measurement.
	10-bit	
	12-bit	
	14-bit	
Frequency for Periodic Measurement	0.4Hz	Specify the frequency of periodic measurement. Measurements proceed at the specified frequency.
	1Hz	
	2Hz	
Callback	<code>hs400x_callback</code>	Specify the name of the user callback function. A callback function name conforming to the C language standard can be specified. When "NULL" is specified, no callback function is used.

5.1.2 RX Family

Select the `r_hs400x_rx` component on the [Component] tabbed page of the Smart Configurator, and the configurable items will be shown in the [Configure] panel.

The following items and values can be specified.

Table 5-2 HS400x Settings for the RX Family MCU

設定項目	設定値	説明
Configurations		
Parameter Checking	System Default	Enable or disable the parameter check processing. When "Enabled" is selected, the project is built so that the generated code includes the parameter check processing.
	Enabled	
	Disabled	
Number of HS400X sensors	1	Specify the number of HS400X sensors to be connected.
	2	
Measurement Type of HS400X sensors	Hold Measurement	Specify the type of measurement. Select from among "Hold Measurement" (one-shot measurement), "No-Hold Measurement", or "Periodic Measurement" (sequential measurement).
	No-Hold Measurement	
	Periodic Measurement	
Data Types of HS400X sensors	Both humidity and temperature	Specify the type of data to be acquired from the sensor. Both the humidity and temperature or the humidity alone can be selected.
	Temperature only	
I2C Communication device No. for HS400X sensor device x (x = 0 or 1)	I2C Communication Device(y) (y = 0 - 15)	Specify the communication line to be used by the sensor.
Temperature Resolution for HS400X sensor device x (x = 0 or 1)	8-bit	Specify the resolution of temperature measurement.
	10-bit	
	12-bit	
	14-bit	
Humidity Resolution for HS400X sensor device x (x = 0 or 1)	8-bit	Specify the resolution of humidity measurement.
	10-bit	
	12-bit	
	14-bit	
Frequency for Periodic Measurement for HS400X sensor device x (x = 0 or 1)	0.4Hz	Specify the frequency of periodic measurement. Measurements proceed at the specified frequency.
	1Hz	
	2Hz	
Callback function for HS400X sensor device x (x = 0 or 1)	hs400x_user_callback(x) (x = 0 or 1)	Specify the name of the user callback function. A callback function name conforming to the C language standard can be specified.

5.1.3 RL78 Family

Settings can be modified by changing the values of constants defined in the `\r_config\r_hs400x_rl_config.h` file in the project tree of the sample project.

The following items and values can be specified.

Table 5-3 HS400x Settings for the RL78 Family MCU

Constant Name	Value	Description
Configurations		
RM_HS400X_CFG_PARAM_CHECKING_ENABLE	0	Specify whether to include the processing to check parameters in the code to be generated. When "0" is specified, the generated code does not include the processing to check parameters. When "1" is specified, the generated code includes the processing to check parameters.
	1	
RM_HS400X_CFG_DEVICE_NUM_MAX	1	Specify the number of HS400x sensors to be connected.
	2	
RM_HS400X_CFG_MEASUREMENT_TYPE	0	Specify the type of measurement. Select from among "Hold Measurement" (0) (one-shot measurement), "No-Hold Measurement" (1), or "Periodic Measurement" (2) (sequential measurement).
	1	
	2	
RM_HS400X_CFG_DATA_BOTH_HUMIDITY_TEMPERATURE	0	Specify the type of data to be acquired from the sensor. The humidity alone (0) or both the humidity and temperature (1) can be selected.
	1	
RM_HS400X_CFG_DEVICE_COMMS_INSTANCE (x = 0 or 1)	g_comms_i2c_device(x) (x = 0 or 1)	Specify the instance name of the communications line to be used.
RM_HS400X_CFG_DEVICE_CALLBACK (x = 0 or 1)	hs400x_user_callback(x) (x = 0 or 1)	Specify the name of the user callback function. A callback function name conforming to the C language standard can be specified.
RM_HS400X_CFG_DEVICE_TEMPERATURE_RESOLUTION (x = 0 or 1)	RM_HS400X_TEMPERATURE_RESOLUTION_8BIT	Specify the resolution of humidity measurement.
	RM_HS400X_TEMPERATURE_RESOLUTION_10BIT	
	RM_HS400X_TEMPERATURE_RESOLUTION_12BIT	
	RM_HS400X_TEMPERATURE_RESOLUTION_14BIT	

RM_HS400X_CFG_DEVICE_HUMIDITY_RESOLUTION (x = 0 or 1)	RM_HS400X_HUMIDITY_RESOLUTION_8BIT	Specify the resolution of temperature measurement.
	RM_HS400X_HUMIDITY_RESOLUTION_10BIT	
	RM_HS400X_HUMIDITY_RESOLUTION_12BIT	
	RM_HS400X_HUMIDITY_RESOLUTION_14BIT	
RM_HS400X_CFG_DEVICE_PERIODIC_MEASUREMENT_FREQUENCY (x = 0 or 1)	RM_HS400X_PERIODIC_MEASUREMENT_FREQUENCY_0P4HZ	Specify the frequency of periodic measurement. Measurements proceed at the specified frequency.
	RM_HS400X_PERIODIC_MEASUREMENT_FREQUENCY_1HZ	
	RM_HS400X_PERIODIC_MEASUREMENT_FREQUENCY_2HZ	

5.1.4 RZ Family

Select the `rm_hs400x` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-4 HS400x Settings for the RZ Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Measurement Type	Hold Measurement	Specify the type of measurement. Select from among "Hold Measurement" (one-shot measurement), "No-Hold Measurement", or "Periodic Measurement" (sequential measurement).
	No-Hold Measurement	
	Periodic Measurement	
Data type	Both humidity and temperature	Specify the type of data to be acquired from the sensor. Both the humidity and temperature or the humidity alone can be selected.
	Humidity only	
Module <code>g_hs400x_sensor</code> HS400X on <code>rm_hs400x</code>		
Name	<code>g_hs400x_sensor0</code>	Specify the name of the module. A module name conforming to the C language standard can be specified.
Temperature Resolution	8-bit	Specify the resolution of temperature measurement.
	10-bit	
	12-bit	
	14-bit	
Humidity Resolution	8-bit	Specify the resolution of humidity measurement.
	10-bit	
	12-bit	
	14-bit	
Frequency for Periodic Measurement	0.4Hz	Specify the frequency of periodic measurement. Measurements proceed at the specified frequency.
	1Hz	
	2Hz	
Callback	<code>hs400x_callback</code>	Specify the name of the user callback function. A callback function name conforming to the C language standard can be specified. When "NULL" is specified, no callback function is used.

5.2 Sensor Communication Middleware Settings

5.2.1 RA Family

Select the `rm_comms_i2c` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-5 Communication Middleware Settings for the RA Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Module <code>g_comms_i2c_device</code> I2C Communication Device on <code>rm_comms_i2c</code>		
Name	<code>g_comms_i2c_device0</code>	Specify the name of the module. A module name conforming to the C language standard can be specified.
Semaphore Timeout	<code>0xFFFFFFFF</code>	For an RTOS project, specify the time of semaphore timeout.
Slave Address	<code>0x54</code>	Specify the slave address. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Address Mode	7-Bit	Specify the number of slave address bits. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Callback	<code>rm_hs400x_callback</code>	Specify the name of the user callback function. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Module <code>g_comms_i2c_bus0</code> I2C Shared Bus on <code>rm_comms_i2c</code>		
Name	<code>g_comms_i2c_bus0</code>	Specify the name of the I2C module.
Bus Timeout	<code>0xFFFFFFFF</code>	Specify the time of I2C bus timeout.
Semaphore for blocking	Unuse	For an RTOS project, enable or disable processing for blocking.
	Use	
Recursive Mutex for Bus	Unuse	For an RTOS project, enable or disable recursive operation when blocking is enabled.
	Use	

5.2.2 RX Family

Select the `r_comms_i2c_rx` component on the [Component] tabbed page of the Smart Configurator, and the configurable items will be shown in the [Configure] panel.

The following items and values can be specified.

Table 5-6 Communication Middleware Settings for the RX Family MCU

Configurable Item	Value	Description
Configurations		
Parameter Checking	System Default	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Number of I2C Shared Buses	Unused	Specify the number of I2C bus lines that can be connected.
	1	
	2 – 16	
Number of I2C Devices	Unused	Specify the number of I2C devices that can be connected.
	1	
	2 – 16	
Blocking operation supporting with RTOS	Disabled	For an RTOS project, enable or disable the blocking operation.
	Enabled	
Bus lock operation supporting with RTOS	Disabled	For an RTOS project, enable or disable the bus lock operation.
	Enabled	
IIC Driver Type for I2C Shared bus(x) (x = 0 – 15)	RIIC	Specify the I2C type to be used for the communications bus. Using the RIIC requires <code>r_riic_rx</code> . Using the SCI IIC requires <code>r_sci_iic_rx</code> . If an unused FIT module is deleted, a warning message will appear but this will not affect the operation.
	SCI IIC	
	Not selected	
Channel No. for I2C Shared bus(x) (x = 0 – 15)	0	Specify the I2C channel number to be used for the communications bus.
Timeout for the bus lock of the I2C bus for I2C Shared Bus(x) (x = 0 – 15)	0xFFFFFFFF	Specify the time of I2C bus lock timeout for I2C bus x. (x = 0 – 15)
I2C Shared Bus No. for I2C Communication Device(x) (x = 0 – 15)	I2C Shared Bus(x) (x = 0 – 15)	Specify the configuration of the I2C bus to be used for the communications bus.
Slave address for communication device(x) (x = 0 – 15)	0x54	Specify the slave address of the device to be connected to the communications bus. When using <code>r_hs400x_rx</code> , specify 0x54.
Slave address mode for communication device(x) (x = 0 – 15)	7 bit address mode	Specify the slave address mode. When using <code>r_hs400x_rx</code> , specify the 7-bit address mode.
Callback function for Communication device(x) (x = 0 – 15)	<code>comms_i2c_user_callback(x)</code> (x = 0 – 15)	Specify the name of the user callback function. When using <code>r_hs400x_rx</code> , specify <code>rm_hs400x_callback(y)</code> (y = 0).

5.2.3 RL78 Family

Settings can be modified by changing the values of constants defined in the `\r_config\r_comms_i2c_rl_config.h` file in the project tree of the sample project.

The following items and values can be specified.

Table 5-7 Communication Middleware Settings for the RL78 Family MCU

Constant Name	Value	Description
Configurations		
COMMS_I2C_CFG_PARAMETER_CHECKING_ENABLE	0	Specify whether to include the processing to check parameters in the code to be generated. When "0" is specified, the generated code does not include the processing to check parameters. When "1" is specified, the generated code includes the processing to check parameters.
	1	
COMMS_I2C_CFG_BUS_NUM_MAX	1	Specify the number of communications bus lines that can be connected.
	2	
	3	
	4	
	5	
COMMS_I2C_CFG_DEVICE_NUM_MAX	1	Specify the number of I2C devices that can be connected.
	2	
	3	
	4	
	5	
COMMS_I2C_CFG_BUS(x)_DRIVER_TYPE (x = 0 – 4)	COMMS_DRIVER_I2C	Specify the I2C type to be used for the communications bus.
	COMMS_DRIVER_SAU_I2C	
COMMS_I2C_CFG_DEVICE(x)_BUS_CH (x = 0 – 4)	g_comms_i2c_bus(x)_extended_cfg (x = 0 – 4)	Specify the configuration of the I2C bus to be used for the communications bus.
COMMS_I2C_CFG_DEVICE(x)_SLAVE_ADDR (x = 0 – 4)	0x54	Specify the slave address of the device to be connected to the communications bus. When using <code>rm_hs400x</code> , specify 0x54.
COMMS_I2C_CFG_DEVICE(x)_CALLBACK (x = 0 – 4)	comms_i2c_user_callback(x) (x = 0 – 4)	Specify the name of the user callback function. When using <code>rm_hs400x</code> , specify <code>rm_hs400x_callback(y)</code> (y = 0 or 1).

5.2.4 RZ Family

Select the `rm_comms_i2c` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-8 Communication Middleware Settings for the RZ Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Module <code>g_comms_i2c_device</code> I2C Communication Device on <code>rm_comms_i2c</code>		
Name	<code>g_comms_i2c_device0</code>	Specify the name of the module. A module name conforming to the C language standard can be specified.
Semaphore Timeout	<code>0xFFFFFFFF</code>	For an RTOS project, specify the time of semaphore timeout.
Slave Address	<code>0x54</code>	Specify the slave address. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Address Mode	7-Bit	Specify the number of slave address bits. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Callback	<code>rm_hs400x_callback</code>	Specify the name of the user callback function. When <code>rm_hs400x</code> is used, this value is automatically specified and cannot be modified.
Module <code>g_comms_i2c_bus0</code> I2C Shared Bus on <code>rm_comms_i2c</code>		
Name	<code>g_comms_i2c_bus0</code>	Specify the name of the I2C module.
Bus Timeout	<code>0xFFFFFFFF</code>	Specify the time of I2C bus timeout.
Semaphore for blocking	Unuse	For an RTOS project, enable or disable processing for blocking.
	Use	
Recursive Mutex for Bus	Unuse	For an RTOS project, enable or disable recursive operation when blocking is enabled.
	Use	

5.3 I2C Driver Settings

5.3.1 RA Family

Select the `r_iic_master`, `r_sci_i2c` or `r_sau_i2c` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-9 r_iic_master Settings for the RA Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
DTC on Transmission and Reception	Enabled	Specify whether to use the DTC in transmission and reception.
	Disabled	
10-bit slave addressing	Enabled	Specify whether to support 10-bit slave addresses. When using <code>rm_hs400x</code> , select "Disabled".
	Disabled	
Module g_i2c_master0 I2C Master (r_iic_master)		
Name	<code>g_i2c_master0</code>	Specify the name of the module.
Channel	0	Specify the channel number to be used.
Rate	Standard	Specify the bit rate. When using <code>rm_hs400x</code> , select "Standard" or "Fast-mode".
	Fast-mode	
	Fast-mode plus	
Rise Time (ns)	120	Specify the time for the SCL signal to rise according to the specifications of the target board to be used.
Fall Time (ns)	120	Specify the time for the SCL signal to fall according to the specifications of the target board to be used.
Duty Cycle (%)	50	Specify the SCL duty cycle.
Slave Address	0x00	This item specifies the slave address of the device to be connected but the user does not need to make this setting because <code>rm_comms_i2c</code> overwrites any setting made here.
Address Mode	7-Bit	This item specifies the slave address mode for the device to be connected but the user does not need to make this setting because <code>rm_comms_i2c</code> overwrites any setting made here.
	10-Bit	
Timeout Mode	Short Mode	Specify the time of I2C bus timeout.
	Long Mode	
Callback	<code>rm_comms_i2c_callback</code>	The name of the user callback function is automatically specified by <code>rm_comms_i2c</code> .

Interrupt Priority Level	Priority 0 (highest)	Specify the interrupt priority level of the I2C bus driver.
	Priority 1	
	Priority 2	
	Priority 3	
	Priority 4	
	Priority 5	
	Priority 6	
	Priority 7	
	Priority 8	
	Priority 9	
	Priority 10	
	Priority 11	
	Priority 12	
	Priority 13	
	Priority 14	
Priority 15		
Pins		
SDA	Pxxx	The pin numbers to be used by the driver are displayed. Use the [Pins] tabbed page to modify the pin configuration.
SCL	Pxxx	

Table 5-10 r_sci_i2c Settings for the RA Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
DTC on Transmission and Reception	Enabled	Specify whether to use the DTC in transmission and reception.
	Disabled	
10-bit slave addressing	Enabled	Specify whether to support 10-bit slave addresses. When using rm_hs400x, select "Disabled".
	Disabled	
Module g_i2c0 I2C Master (r_sci_i2c)		
Name	g_i2c0	Specify the name of the module.
Channel	0	Specify the channel number to be used.
Slave Address	0x00	This item specifies the slave address of the device to be connected but the user does not need to make this setting because rm_comms_i2c overwrites any setting made here.
Address Mode	7-Bit	This item specifies the salve address mode for the device to be connected but the user does not need to make this setting because rm_comms_i2c overwrites any setting made here.
	10-bit	
Rate	Standard	Specify the bit rate. Select "Standard" or "Fast-mode".
	Fast-mode	
	Fast-mode plus	
SDA Output Delay (nano seconds)	300	Specify the SDA output delay time.
Noise filter setting	Use clock signal divided by 1 with noise filter	Specify the noise filter to be used for input signals.
	Use clock signal divided by 2 with noise filter	
	Use clock signal divided by 4 with noise filter	
	Use clock signal divided by 8 with noise filter	
Bit Rate Modulation	Enable	Enable or disable the bit rate modulation function.
	Disable	
Callback	rm_comms_i2c_callback	The name of the user callback function is automatically specified by rm_comms_i2c.

Interrupt Priority Level	Priority 0 (highest)	Specify the interrupt priority level of the I2C bus driver.
	Priority 1	
	Priority 2	
	Priority 3	
	Priority 4	
	Priority 5	
	Priority 6	
	Priority 7	
	Priority 8	
	Priority 9	
	Priority 10	
	Priority 11	
	Priority 12	
	Priority 13	
	Priority 14	
Priority 15		
RX Interrupt Priority Level [Only used when DTC is enabled]	Priority 0 (highest)	When using the DTC, specify the priority level of the reception interrupt.
	Priority 1	
	Priority 2	
	Priority 3	
	Priority 4	
	Priority 5	
	Priority 6	
	Priority 7	
	Priority 8	
	Priority 9	
	Priority 10	
	Priority 11	
	Priority 12	
	Priority 13	
	Priority 14	
Priority 15		
Disabled		
Pins		
SDA	Pxxx	The pin numbers to be used by the driver are displayed. Use the [Pins] tabbed page to modify the pin configuration.
SCL	Pxxx	

Table 5-11 r_sau_i2c Settings for the RA Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Specify whether to include the processing to check parameters in the code to be generated. When "Disabled" is selected, the generated code does not include the processing to check parameters. When "Enabled" is selected, the generated code includes the processing to check parameters.
	Enabled	
	Disabled	
Enable Critical Section	Enabled	Set enable or disable of critical section. When using multiple channels on the same SAU unit, specify Enabled.
	Disabled	
Manual Start-Stop	Enabled	Specify whether the user calls the start condition and stop condition function. When "Disabled" is selected, the generated code does not include calls to the start condition and stop condition function. When "Enabled" is selected, the generated code includes calls to the start condition and stop condition function.
	Disabled	
Enable Single Channel	00	Does not include processing other than the specified channel. When "Disabled" is selected, all channels are supported.
	20	
	Disabled	
DTC Support	Enabled	Specify whether to support the DTC.
	Disabled	
Module g_i2c0 I2C Master (r_sau_i2c)		
Name	g_i2c0	Specify the name of the module.
Channel	20	Specify the channel number to be used.
Operation clock	CK0	Specify the I2C operation clock.
	CK1	
Slave Address	0x00	This item specifies the slave address of the device to be connected but the user does not need to make this setting because rm_comms_i2c overwrites any setting made here.
Rate	Standard	Specify the bit rate. Select "Standard" or "Fast-mode".
	Fast-mode	
	Fast-mode plus	
Delay time (Microseconds)	5	Specify the SDA output delay time.
Callback	rm_comms_i2c_callback	The name of the user callback function is automatically specified by rm_comms_i2c.
Transfer end interrupt priority	Priority 0 (highest)	Specify the interrupt priority level of the I2C bus driver.
	Priority 1	
	Priority 2	
	Priority 3	

Pins		
SCL	Pxxx	The pin numbers to be used by the driver are displayed. Use the [Pins] tabbed page to modify the pin configuration.
SDA	Pxxx	

5.3.2 RX Family

Select the `r_riic_rx` or `r_sci_iic_rx` component on the [Component] tabbed page of the Smart Configurator, and the configurable items will be shown in the [Configure] panel.

The following items and values can be specified.

Table 5-12 `r_riic_rx` Settings for the RX Family MCU

Configurable Item	Value	Description
Configurations		
Set parameter checking enable	System Default	Specify whether to include the processing to check parameters in the code to be generated. When "Not" is selected, the generated code does not include the processing to check parameters. When "Include" is selected, the generated code includes the processing to check parameters.
	Not	
	Include	
MCU supported channels for CHx (x = 0 – 2)	Not supported	Specify whether to use channel x. When a channel is not to be used, select "Not supported". When "Not supported" is selected, the generated code does not include processing for the given channel. When "Supported" is selected, the generated code includes processing for the given channel.
	Supported	
CHx RIIC bps(kbps) (x = 0 – 2)	400	Specify the bit rate. Set this to a value no greater than 400 when using <code>rm_hs400x</code> .
Digital filter for CHx (x = 0 – 2)	Not	Specify the number of stages in the noise filter for the specified channel. When "Not" is selected, the noise filter is disabled.
	One IIC phi	
	Two IIC phi	
	Three IIC phi	
	Four IIC phi	
Setting port setting processing	Not include port setting	Specify whether to include the settings for using port pins as the SCL and SDA pins in the code to be generated. When "Not include port setting" is selected, the generated code does not include the processing for setting port pins to serve as serial pins. When "Include port setting" is selected, the generated code includes the processing for setting port pins to serve as serial pins.
	Include port setting	
Master arbitration lost detection function for CHx (x = 0 – 2)	Unused	Enable or disable the master loss-in-arbitration detection function for the specified channel. When using multiple masters, select "Used" (enabled). When "Unused" is selected, master loss-in-arbitration detection is disabled. When "Used" is selected, master loss-in-arbitration detection is enabled.
	Used	
Address y format for CHx (x = 0 – 2, y = 0 – 2)	Not	Specify whether to support 7-bit addressing or 10-bit addressing for the slave address of the specified RIIC. When using <code>rm_hs400x</code> , select "7 bit address format".
	7 bit address format	
	10 bit address format	

Slave Address y for CHx (x = 0 – 2, y = 0 – 2)	0x0025	This item specifies the slave address for the specified channel but the user does not need to make this setting because rm_comms_i2c overwrites any setting made here.
General call address for CHx	Unused Used	Enable or disable the use of the general call address with the specified channel. When "Unused" is selected, the use of the general call address is disabled. When "Used" is selected, the use of the general call address is enabled.
CHx RXI INT Priority Level (x = 0 – 2)	Level 1 Level 2 Level 3 Level 4 Level 5 Level 6 Level 7 Level 8 Level 9 Level 10 Level 11 Level 12 Level 13 Level 14 Level 15 (highest)	Specify the priority level of the reception data full interrupt (RXI) for the specified channel. Specify a level from 1 to 15.
CHx TXI INT Priority Level (x = 0 – 2)	Level 1 Level 2 Level 3 Level 4 Level 5 Level 6 Level 7 Level 8 Level 9 Level 10 Level 11 Level 12 Level 13 Level 14 Level 15 (highest)	Specify the priority level of the transmission data empty interrupt (TXI) for the specified channel. Specify a level from 1 to 15.
CHx EEI INT Priority Level (x = 0 – 2)	Level 1 Level 2 Level 3 Level 4 Level 5 Level 6 Level 7 Level 8 Level 9 Level 10 Level 11	Specify the priority level of the communication error or event generation interrupt (EEI) for the specified channel. Specify a level from 1 to 15.

	<ul style="list-style-type: none"> Level 12 Level 13 Level 14 Level 15 (highest) 	
CHx TEI INT Priority Level (x = 0 – 2)	<ul style="list-style-type: none"> Level 1 <li style="background-color: #d9ead3;">Level 2 Level 3 Level 4 Level 5 Level 6 Level 7 Level 8 Level 9 Level 10 Level 11 Level 12 Level 13 Level 14 Level 15 (highest) 	Specify the priority level of the transmission end interrupt (TEI) for the specified channel. Specify a level from 1 to 15.
Timeout function for CHx (x = 0 – 2)	<ul style="list-style-type: none"> Unused <li style="background-color: #d9ead3;">Used 	Enable or disable the timeout detection function for the specified channel. When "Unused" is selected, timeout detection is disabled. When "Used" is selected, timeout detection is enabled.
Timeout detection time for CHx (x = 0 – 2)	<ul style="list-style-type: none"> <li style="background-color: #d9ead3;">Long mode Short mode 	Specify the time for timeout detection for the specified channel.
Count up during low period of timeout detection for CHx (x = 0 – 2)	<ul style="list-style-type: none"> Unused <li style="background-color: #d9ead3;">Used 	Enable or disable incrementing of the internal counter for detecting a timeout while the SCL signal is at the low level when the timeout detection function is enabled for the specified channel. When "Unused" is selected, incrementing of the counter while the SCL signal is at the low level is disabled. When "Used" is selected, incrementing of the counter while the SCL signal is at the low level is enabled.
Count up during high period of timeout detection for CHx (x = 0 – 2)	<ul style="list-style-type: none"> Unused <li style="background-color: #d9ead3;">Used 	Enable or disable incrementing of the internal counter for detecting a timeout while the SCL signal is at the high level when the timeout detection function is enabled for the specified channel. When "Unused" is selected, incrementing of the counter while the SCL signal is at the high level is disabled. When "Used" is selected, incrementing of the counter while the SCL signal is at the high level is enabled.
Set Counter of checking bus busy	1000	The value of the timeout counter (the counter for bus checking) to be used in the processing of checking the bus busy state by API functions can be specified by software.

Resources

SDAx Pins	Checked	Specify the pins to be used. Select the checkboxes for the desired pins.
SCLx Pins	Checked	

Table 5-13 r_sci_iic_rx Settings for the RX Family MCU

Configurable Item	Value	Description
Configurations		
Set parameter checking enable	System Default	Specify whether to include the processing to check parameters in the code to be generated. When "Not" is selected, the generated code does not include the processing to check parameters. When "Include" is selected, the generated code includes the processing to check parameters.
	Not	
	Include	
MCU supported channels for CHx (x = 0 – 12)	Not supported	Specify whether to use channel x. When "Not supported" is selected, the generated code does not include processing for the given channel. When "Supported" is selected, the generated code includes processing for the given channel.
	Supported	
SCI IIC bitrate (bps) for CHx (x = 0 – 12)	384000	Specify the bit rate. Set to 384000 (384 Kbits/s) or a smaller value.
Interrupt Priority for CHx (x = 0 – 12)	Level 1	Specify the priority level of interrupts triggered by the detection of a start or stop condition, reception, transmit data empty, and transmit end. Specify a level from 1 to 15.
	Level 2	
	Level 3	
	Level 4	
	Level 5	
	Level 6	
	Level 7	
	Level 8	
	Level 9	
	Level 10	
	Level 11	
	Level 12	
	Level 13	
	Level 14	
	Level 15 (highest)	
Digital noise filter (NFEN bit) for CHx (x = 0 – 12)	Disable	Specify whether to use the noise cancellation function for the SSCL and SSSDA input signals. When "Disable" is selected, the noise cancellation function is disabled. When "Enable" is selected, the noise cancellation function is enabled.
	Enable	
Noise Filter Setting Register (NFCS bit) for CHx (x = 0 – 12)	The clock divided by 1	Specify the sampling clock of the digital noise filter.
	The clock divided by 2	
	The clock divided by 4	
	The clock divided by 8	
I2C Mode Register 1 (IICDL bit) for CHx (x = 0 – 12)	18	Specify the number of SSSDA output delay cycles from the falling edge of the SSCL output. Specify a value from 1 to 31.
Software bus busy check counter	1000	Specify the counter value to be judged to represent the bus busy state. The value of the timeout counter (the counter for bus checking) to be used in the processing of checking the bus busy state by API functions for the simplified I2C can be specified by software.

Setting port setting processing	Not include port setting Include port setting	Specify whether to include the settings for using port pins as the SSCL and SSDA pins in the code to be generated. When "Not include port setting" is selected, the generated code does not include the processing for setting port pins to serve as serial pins. When "Include port setting" is selected, the generated code includes the processing for setting port pins to serve as serial pins.
Resources		
SSDAx Pins	Checked	Specify the pins to be used.
SSCLx Pins	Checked	Select the checkboxes for the desired pins.

5.3.3 RL78 Family

Select "Serial" from the peripheral functions in the Code Generator, and the configurable items will be shown on the [Peripheral Functions] tabbed page.

The following items and values can be specified.

Table 5-14 Serial Settings for the RL78 Family MCU

Configurable Item	Value	Description
SAUx		
Channel		
Channel x	Unused	Specify the communication function of the channel to be used. When using r_hs400x, select IICxx.
	UARTxx	
	CSIxx	
	IICxx	
IICxx		
Transfer rate	1000000	Specify the bit rate. When using rm_hs400x, specify 100000.
Transfer end interrupt priority (INTIICxx)	High	Specify the priority level of the transfer end interrupt.
	Level1	
	Level2	
	Low	
Master transmission end	Checked	Specify whether to use the callback function when master transmission ends.
Master reception end	Checked	Specify whether to use the callback function when master reception ends.
Master error	Checked	Specify whether to use the callback function when a communication error occurs.
IICAx		
Transfer mode		
Transfer mode	Unused	Specify the communication function of the channel to be used. Select "Single master".
	Single master	
	Slave	
Setting		
Clock mode setting	fCLK	Specify the clock to drive counting.
	fCLK/2	
Address	16	Specify the local address.
Operation mode setting	Standard	Specify the operating mode.
	Fast mode/Fast mode plus	
Transfer clock (fSCL)	100000	Specify the bit rate. Set to 400000 or a smaller value.
Communication end interrupt priority (INTIICAx)	High	Specify the priority level of the communication end interrupt.
	Level1	
	Level2	
	Low	
Master transmission end	Checked	Specify whether to use the callback function when master transmission ends.
Master reception end	Checked	Specify whether to use the callback function when master reception ends.
Master error	Checked	Specify whether to use the callback function when a communication error occurs.

Generated stop condition in master transmission/reception end callback function	Checked	Specify whether to generate a stop condition in the callback function. Deselect the checkbox.
---	---------	--

5.3.4 RZ Family

Select the `r_iic_master` or `r_sci_i2c` stack on the [Stack] tabbed page of the FSP Configurator, and the configurable items will be shown on the [Properties] tabbed page.

The following items and values can be specified.

Table 5-15 `r_iic_master` Settings for the RZ Family MCU

Configurable Item	Value	Description
Common		
Parameter Checking	Default (BSP)	Enable or disable the parameter check processing. When "Enabled" is selected, the project is built so that the generated code includes the parameter check processing.
	Enabled	
	Disabled	
DTC on Transmission and Reception	Enabled	Specify whether to use the DTC in transmission and reception.
	Disabled	
10-bit slave addressing	Enabled	Specify whether to support 10-bit slave addresses. If you are using <code>rm_hs400x</code> , select "Disabled".
	Disabled	
Module <code>g_i2c_master0</code> I2C Master Driver on <code>r_iic_master</code>		
Name	<code>g_i2c_master0</code>	Specify the name of the module.
Channel	0	Specify the channel number to be used.
Rate	Standard	Specify the bit rate. If you are using <code>rm_hs400x</code> , select "Standard" or "Fast-mode".
	Fast-mode	
	Fast-mode plus	
Rise Time (ns)	120	Specify the SCL rise time to suit the specifications of the target board to be used.
Fall Time (ns)	120	Specify the SCL fall time to suit the specifications of the target board to be used.
Duty Cycle (%)	50	Specify the SCL duty cycle.
Noise Filter Stages	1	Removes noise below the 1 IIC ϕ cycle.
	2	Removes noise below the 2 IIC ϕ cycle.
	3	Removes noise below the 3 IIC ϕ cycle.
	4	Removes noise below the 4 IIC ϕ cycle.
Slave Address	0x00	This item specifies the slave address of the device to be connected but the user does not need to make this setting because any setting that is made here is overwritten by the setting in <code>rm_comms_i2c</code> .
Address Mode	7-Bit	This item specifies the slave address mode for the device to be connected but the user does not need to make this setting because any setting that is made here is overwritten by the setting in <code>rm_comms_i2c</code> .
	10-Bit	
Timeout Mode	Short Mode	Specify the time of I2C bus timeout.
	Long Mode	

Callback	rm_comms_i2c_callback	The name of the user callback function is automatically specified by rm_comms_i2c.
Interrupt Priority Level	Priority 0 (highest)	Specify the interrupt priority level of the I2C bus driver.
	Priority 1	
	Priority 2	
	Priority 3	
	Priority 4	
	Priority 5	
	Priority 6	
	Priority 7	
	Priority 8	
	Priority 9	
	Priority 10	
	Priority 11	
	Priority 12	
	Priority 13	
	Priority 14	
Priority 15		

6. Guide to Changing the Target Device

Use the following procedures to change the target device to a new one and run a sample project on the new device.

Before switching to a new device, import the original sample project for the current device to the workspace.

6.1 RA Sample Project

Use the following procedures to modify a sample project.

This section describes an example of modifying the "HS400x_RA6M4_NonOS" sample project so that it can be used on the EK-RA2E1 board.


However, when using the I2C driver different from the original sample project, describes for the FPB-RA0E1 board.

The description of PMOD1 is the procedure when using a board to which "OptionType6A" is applied.

6.1.1 Importing the Sample Project


Select [Import] from the menu.

The [Import] window will appear. Select "Rename & Import Existing C/C++ Project into Workspace" in the window and press the [Next] button.




Press the [Browse] button to open the [Select Folder] window.

Select the folder of the original project for the current device from the list of imported sample projects and press the [Select Folder] button.



Enter the project name, select the original project for the current device, and press the [Finish] button.



6.1.2 Modifying Settings of the FSP Configurator


Double-click on "Configurator.xml" in the project tree to open the FSP Configurator.

6.1.2.1 [BSP] Setting

Change the settings of "Board" and "Device" on the [BSP] tabbed page.

When selecting a Renesas board, you will only need to modify the "Board" setting.

When selecting a board provided from other companies, change the "Board" setting to "Custom User Board (Any Device)" and then change the "Device" setting to the new device to be used.




6.1.2.2 [Clocks] Setting

Set up the clocks on the [Clocks] tabbed page.

When "Custom User Board (Any Device)" is selected for "Board", set up the clocks to suit the specifications of the target board to be used.


When a Renesas board is selected for "Board", the clocks are automatically set up.




6.1.2.3 [Pins] Setting

In the [Pins] tabbed page, modify the pin configuration according to the specifications of the target board to be used.

When using a Renesas board, change the selection for "Select Pin Configuration" from "RA6M4 EK" to the target board; appropriate pins will be automatically assigned.



If the desired board is not displayed in the drop-down list for "Select Pin Configuration", click on [Manage Configuration] to open the [Manage Pin Configurations] window and select the desired board in the window.




However, the "Select Pin Configuration" assignment will apply the SPI communication pin settings that support PMOD Type 2A on the EK-RA2E1 board.

This sample software uses PMOD Type 6A, therefore it is necessary to change the I2C communication pin settings that support PMOD Type 6A.

SCI2 is assigned to PMOD1 and SCI1 to PMOD2 on the EK-RA2E1 board.

I2C communication is assigned to P301 and P302 on PMOD1(OptionType6A), and it is assigned to P401 and P402 on PMOD2.

After automatic assignment of "Select Pin Configuration", reconfigure in "Pin Configuration".



To enable generation of pin settings, check [Generate data] check-box and enter a desired name in the text field.

The entered name is linked to the pin configuration, therefore must use a unique name that does not duplicate with other pin configurations.

In our example, it is "g_bsp_pin_cfg_2e1".

The screenshot shows the 'Pin Configuration' software interface. At the top, the window title is '[HS400x_RA2E1_NonOS] FSP Configuration'. The main title is 'Pin Configuration'. There is a 'Generate Project Content' button. Below that, there are buttons for 'Export to CSV file' and 'Configure Pin Driver Warnings'. A dropdown menu shows 'RA2E1 EK' with a 'Manage configurations...' link. A checked box 'Generate data:' is followed by a text input field containing 'g_bsp_pin_cfg_2e1'. The interface is split into two panes: 'Pin Selection' on the left and 'Pin Configuration' on the right. The 'Pin Selection' pane has a search filter and a tree view with categories like 'Ports' (P0-P9, Other Pins) and 'Peripherals' (Analog:ACMP, Analog:ADC, Analog:ANALOG, Connectivity:IIC, Connectivity:SCI, Connectivity:SPI, Input:CTSU, Input:ICU, Input:KINT). The 'Pin Configuration' pane has a table with columns 'Name', 'Value', and 'Link', and a 'Cycle Pin Group' button. At the bottom, there are tabs for 'Pin Function' and 'Pin Number'.

6.1.2.4 [Stacks] Setting

Modify the configuration for individual components on the [Stacks] tabbed page.


Modify the settings of I2C driver to suit the specifications of the target board.

(1) I2C Driver

(a) When using the same I2C driver as the original sample project

SCI2 is assigned to PMOD1 and SCI1 is assigned to PMOD2 on the EK-RA2E1 board.


To use PMOD1, set “Channel” to “2”. To use PMOD2, set to “1”.



(b) When using the different I2C driver as the original sample project

SAU0 is assigned to PMOD1 and SAU1 is assigned to PMOD2 on the FPB-RA0E1 board.

Delete the "I2C Master (r_sci_i2c)" stack and then add the " I2C Master (r_sau_i2c)" stack.



To use PMOD1, set "Channel" to "00". To use PMOD2, set to "20".


Properties Console Renesas Debug ... Debug Search Smart Manual Progress Smart Browser

g_i2c0 I2C Master (r_sau_i2c)

Settings	Property	Value
API Info	Common	
	Parameter Checking	Default (BSP)
	Enable Critical Section	Disabled
	Manual Start-Stop	Disabled
	Enable Single Channel	Disabled
	DTC Support	Disable
	Module g_i2c0 I2C Master (r_sau_i2c)	
	Name	g_i2c0
	Channel	20
	Operation clock	CK0
Slave Address	0x00	
Rate	Standard	
Delay time (Microseconds)	5	
Callback	rm_comms_i2c_callback	
Transfer end interrupt priority	Priority 2	
Pins		
SCL20	P112	
SDA20	P110	

(2) I/O Port

Enter the name linked to the pin configuration to be used for "Pin Configuration Name" of "g_ioport I/O Port". In our example, it is "g_bsp_pin_cfg_2e1".



(3) Others

If an error is displayed in other stacks, modify the specified item according to the displayed error.

Press [Generate Project Content] to generate files.

Build the project.

Select [Debug Configurations] from the menu and modify the debugger settings to suit the specifications of the emulator to be connected to the target board.

6.1.3 Changing the Toolchain Setting

If you want to use a toolchain other than the GCC ARM Embedded toolchain, copy RRA_HS400X.c (for a non-OS system) or hs400x_sensor_thread_entry.c, sensor_thread_common.c, and sensor_thread_common.c (for a FreeRTOS or Azure RTOS system) from this project and create a new project.

6.2 RX Sample Project


Use the following procedures to modify a sample project.

This section describes an example of modifying the "HS400x_RX65N_NonOS" sample project so that it can be used on the RSKRX231 board.

6.2.1 Importing the Sample Project


Select [Import] from the menu.

The [Import] window will appear. Select "Rename & Import Existing C/C++ Project into Workspace" in the window and press the [Next] button.




Press the [Browse] button to open the [Select Folder] window.

Select the folder of the original project for the current device from the list of imported sample projects and press the [Select Folder] button.




Enter the project name, select the original project for the current device, and press the [Finish] button.




6.2.2 Changing the Device


Select the imported project from the project tree and right-click on it to open the context menu. Select [Change Device] from the menu.




Select a desired board or device in the [Change Device] window and press the [Next] button.



If a warning message appears, read it and check if it will create a problem in proceeding with the procedure. Press [Next] to move to the next step.




The changes you have made to the settings will be displayed. Press the [Finish] button to apply the changes to the project.




6.2.3 Modifying Settings of the Smart Configurator


On the project tree, double-click on the .scfg file of the imported project in which the target device has been changed; this will open the Smart Configurator window.



Select the [Board] tabbed page to check that the board and device have been changed correctly.




Set up the clocks on the [Clocks] tabbed page to suit the specifications of the target board to be used.




Modify the settings for individual components on the [Components] tabbed page to suit the specifications of the target board.

As SCI8 is assigned to PMOD on the RSK RX231 board, change the setting of "MCU supported channels for CH2" to "Not supported" and "MCU supported channels for CH8" to "Supported" in r_sci_iic_rx.

Select the checkboxes for "SSCL8 Pin" and "SSDA8 Pin" for "SCI8" under "Resources".




Open the [Pins] tabbed page and check that functions are assigned to the SCI8 pin in the [Pin function] panel.



As the use of PMOD Type 2A (extended SPI) is specified in the RSK RX231 board information, a warning message will appear when I2C is used, but this does not produce any problems.

Connecting a sensor board requires a board for converting the PMOD Type 2A interface to PMOD Type 6A.

Press the [Generate Code] icon to generate code.



Build the project.

Select [Debug Configurations] from the menu and modify the debugger settings to suit the specifications of the emulator to be connected to the target board.

6.2.4 Changing the Toolchain Setting

If you want to use a toolchain other than the CC-RX toolchain, copy RX_HS400X.c (for a non-OS system), main.c and hs400x_sensor_thread_entry.c (for a FreeRTOS system), or hs400x_sensor_thread_entry.c, sensor_thread_common.c, and sensor_thread_common.c (for an Azure RTOS system) from this project and create a new project.

6.3 RL78 Sample Project


Changing the target device within the RL78 family requires creating a new project.

This section describes an example of creating a new project that can be used on the RSK RL78/G1G board.


6.3.1 Creating a New Project

Select [File] → [New] → [Renesas C/C++ project] → [Renesas RL78] from the menu bar.


Select the template "Renesas CC-RL C Executable Project" and press the [Next] button.




Enter the project name ("HS400x_RL78G1G_NonOS" in this example) and press the [Next] button.




Change "Target Device" to a desired device (R5F11EFA in this example) and press the [Next] button.



Select the checkbox for "Use Peripheral Code Generator" and press the [Next] button.




Press the [Finish] button.




6.3.2 Settings of the Code Generator


Modify the pin assignment on the [Pin assignment] tabbed page for "Peripheral Functions" to suit the specifications of the target board to be used.



Modify the clock settings on the [Clock setting] tabbed page for "Peripheral Functions" to suit the specifications of the target board.




Select "Used" for "On-chip debug operation setting" on the [On-chip debug setting] tabbed page for "Peripheral Functions".




To use the serial array unit, set the channel assigned to PMOD on the target board to "IICxx" on the [Channel] tabbed page in the [Serial Array Unit] or [Serial] setting window.


Note: The corresponding pin must be selected as N-ch by [Port].




On the tabbed page for IICxx enabled in the serial array unit, set "Transfer rate" to 400000 or 100000, set "Transfer end interrupt priority" to a desired level, and enable all functions under "Callback function setting".




To use the serial interface IICA, select "Single master" on the [Transfer mode] tabbed page for the channel assigned to PMOD on the target board in the [Serial Interface IICA] or [Serial] setting window.




On the [Setting] tabbed page for the channel set to a single master in the previous step, set "Operation mode setting" to either the combination of "Fast mode" and "400000" or the combination of "Standard" and "100000", set the interrupt priority to a desired level, enable all functions under "Callback function setting", and disable "Callback function enhanced feature setting".



On the [General setting] tabbed page for a desired channel of the timer array unit or a desired TAU of the timer, select "Interval timer" under "Functions".



In the page for the channel set to the interval timer, set "Interval value" to "100 μ s", enable timer interrupts, and set the interrupt priority to a desired level.



Press the [Generate Code] button to generate code.

6.3.3 Modifying the Generated Code

Perhaps Code Generator output destination different from this sample software, because Code Generator version differs depending on the MCU used.

Open `r_cg_sau_user.c`, `r_cg_iica_user.c`, or `r_cg_serial_user.c` and add the following code.

Definition for including `r_comms_i2c_if.h`:

```

/*****
Includes
*****/
#include "r_cg_macrodriver.h"
#include "r_cg_sau.h"
/* Start user code for include. Do not edit comment generated here */
#include "r_comms_i2c_if.h"
/* End user code. Do not edit comment generated here */
#include "r_cg_userdefine.h"

```

Addition of the `rm_comms_i2c_bus0_callback()` function to the callback function:

Specify the "false" parameter for the transmission and reception end callback functions and the "true" parameter for the error callback function.

```

/*****
* Function Name: r_iic00_callback_master_error
* Description  : This function is a callback function when IIC00 master err
* Arguments   : flag -
*              status flag
* Return Value : None
*****/
static void r_iic00_callback_master_error(MD_STATUS flag)
{
    /* Start user code. Do not edit comment generated here */
    rm_comms_i2c_bus0_callback(true);
    /* End user code. Do not edit comment generated here */
}
/*****
* Function Name: r_iic00_callback_master_receiveend
* Description  : This function is a callback function when IIC00 finishes
* Arguments   : None
* Return Value : None
*****/
static void r_iic00_callback_master_receiveend(void)
{
    /* Start user code. Do not edit comment generated here */
    rm_comms_i2c_bus0_callback(false);
    /* End user code. Do not edit comment generated here */
}
/*****
* Function Name: r_iic00_callback_master_sendend
* Description  : This function is a callback function when IIC00 finishes
* Arguments   : None
* Return Value : None
*****/
static void r_iic00_callback_master_sendend(void)
{
    /* Start user code. Do not edit comment generated here */
    rm_comms_i2c_bus0_callback(false);
    /* End user code. Do not edit comment generated here */
}

```

Open `t_cg_tau_user.c` or `r_cg_timer_user.c` and add the following code.

Declaration of external for the `(sensor_name)_delay_callback()` function:

```

/*****
Global variables and functions
*****/
/* Start user code for global. Do not edit comment generated here */
extern void hs400x_delay_callback(void);
/* End user code. Do not edit comment generated here */

```

Addition of the call of the `(sensor_name)_delay_callback()` function to the timer interrupt callback function:

```

/*****
* Function Name: r_tau0_channel0_interrupt
* Description  : This function INTTM00 interrupt service routine.
* Arguments   : None
* Return Value : None
*****/
static void __near r_tau0_channel0_interrupt(void)
{
    /* Start user code. Do not edit comment generated here */
    hs400x_delay_callback();
    /* End user code. Do not edit comment generated here */
}

```

Open `t_cg_tau.c` or `r_cg_timer.c` and add the following code.

Define the `R_TAU0_Channel0_Reset()` function in the user code description part:

```

void R_TAU0_Channel0_Reset(void)
{
    /* function not supported by this module */
}

```

Open `t_cg_tau.h` or `r_cg_timer.h` and add the following code.

Declaration of prototype for the `R_TAU0_Channel0_Reset()` function:

```

/*****
Global functions
*****/
void R_TAU0_Create(void);
void R_TAU0_Channel0_Start(void);
void R_TAU0_Channel0_Stop(void);
/* Start user code for function. Do not edit comment generated here */
void R_TAU0_Channel0_Reset(void);
/* End user code. Do not edit comment generated here */

```

Open `r_cg_main.c` or `r_main.c` and add the following code.

Declaration of prototype for each function:

```

/*****
Global variables and functions
*****/
/* Start user code for global. Do not edit comment generated here */
void g_comms_i2c_bus0_quick_setup(void);
void demo_err(void);

void g_hs400x_sensor0_quick_setup(void);
void start_hs400x_demo(void);
/* End user code. Do not edit comment generated here */

```

Addition of the following code to the `main()` function:

```

/* Open the Bus */
g_comms_i2c_bus0_quick_setup();

/* Open HS400X */
g_hs400x_sensor0_quick_setup();

while (1U)
{
    start_hs400x_demo();
}

```

Define of the `g_comms_i2c_bus0_quick_setup()` function and the `demo_err()` function:

```

void g_comms_i2c_bus0_quick_setup(void)
{
    /* bus has been opened by startup process */
}


void demo_err(void)
{
    while(1)
    {
        // nothing
    }
}

```

6.3.4 Modifying Sample Source Files

Right-click on the "application" "general" "r_bsp" "r_comms_i2c_rl" "r_config" "r_hs400x" folder in the project tree of the "HS400x_RL78G14_NonOS" sample project and select [Copy] from the context menu.

Then, right-click on the "src" folder in the newly created project and select [Paste] from the context menu to paste the copied files to the folder.



Open the "r_comms_i2c_rl_config.h" file in the " r_config" folder and modify the values of the following definitions.

- COMMS_I2C_CFG_BUSx_DRIVER_TYPE
- COMMS_I2C_CFG_BUSx_DRIVER_CH

When channel 0 of the serial array unit is used:

```
/* SPECIFY DRIVER TYPE, CHANNEL NO. */
/* For Bus No.0 */
#define COMMS_I2C_CFG_BUS0_DRIVER_TYPE      (COMMS_DRIVER_SAU_I2C) /*
Driver type of I2C Bus */
#define COMMS_I2C_CFG_BUS0_DRIVER_CH      (0) /* Channel No. */
```

When channel 0 of the serial interface IICA is used:

```
/* SPECIFY DRIVER TYPE, CHANNEL NO. */
/* For Bus No.0 */
#define COMMS_I2C_CFG_BUS0_DRIVER_TYPE      (COMMS_DRIVER_I2C) /* Driver
type of I2C Bus */
#define COMMS_I2C_CFG_BUS0_DRIVER_CH      (0) /* Channel No. */
```

For the other definitions, refer to section [5, Configuration Settings](#).

When "serial array unit", "serial interface IICA", or "timer array unit" is used as a peripheral function name in the code generator, modify the sample source code as follows.

src/general/r_smc_entry.h


Modify "r_cg_serial.h" to "r_cg_sau.h" or "r_cg_iica.h":

Modify "r_cg_timer.h" to "r_cg_tau.h":

```
/******
Includes
*****
#include "r_cg_macrodriver.h"
#include "r_cg_sau.h"
#include "r_cg_tau.h"
#include "r_cg_port.h"
#include "r_cg_cgc.h"
#include "r_cg_userdefine.h"
*****
```

Open the [Properties] window for the project.






Select [C/C++ Build] → [Settings] in the [Properties] window to open the [Settings] panel.



Select [Compiler] → [Source] on the [Tool Settings] tabbed page and press the [Add] icon.


Press the [Workspace] button in the [Add directory path] dialog box and a list of projects will appear. Select the "src" folder for the newly created project from the list and press the [OK] button.

Select the checkbox for "Add subdirectories" and press the [OK] button.



Select [Compiler] → [Source] → [Language] on the [Tool Settings] tabbed page and change the setting of "Language standard of C language" to "C99 language standard".

Press the [Apply and Close] button to close the [Properties] window.



Build the project.

Select [Debug Configurations] from the menu and modify the debugger settings to suit the specifications of the emulator to be connected to the target board.

6.4 RZ Sample Project


Use the following procedures to modify a sample project.

This section describes how to modify the "HS400x_RZG2L_NonOS" sample project so that it can be used on the RZ/G2L Evaluation Kit (SMARC) board as an example.

6.4.1 Importing the Sample Project


Select [Import] from the menu.

The [Import] window will appear. Select "Rename & Import Existing C/C++ Project into Workspace" in the window and press the [Next] button.




Press the [Browse] button to open the [Select Folder] window.

Select the folder of the original project for the current device from the list of imported sample projects and press the [Select Folder] button.



Enter the project name, select the original project for the current device, and press the [Finish] button.




6.4.2 Modifying Settings of the FSP Configurator

Double-click on "Configurator.xml" in the project tree to open the FSP Configurator.

Change the settings of "Board" and "Device" on the [BSP] tabbed page.

When selecting a Renesas board, you will only need to modify the "Board" setting.


When selecting a board provided from other companies, change the "Board" setting to "Custom User Board (Any Device)" and then change the "Device" setting to the new device to be used.



Set up the clocks on the [Clocks] tabbed page.

When "Custom User Board (Any Device)" is selected for "Board", set up the clocks to suit the specifications of the target board to be used.

When a Renesas board is selected for "Board", the clocks are automatically set up.





Modify the configuration of individual components on the [Stacks] tabbed page.

Modify the settings for `r_iic_master` to suit the specifications of the target board.

On the RZ/G2L Evaluation Kit (SMARC) board, PMOD1 is assigned RIIC3.

If you are using PMOD1, set channel to 3.



Press [Generate Project Content] to generate files.

Build the project.

Select [Debug Configurations] from the menu and modify the debugger settings to suit the specifications of the emulator to be connected to the target board.

6.4.1 Changing sample code

Open `pin_data.c` in the `src` folder and change the `g_bsp_pin_cfg_data` settings to match the board you are using.

On the RZ/G2L Evaluation Kit (SMARC) board, PMOD1 is assigned RIIC3.

If you are using PMOD1, set the P18_0 to RIIC3_SDA (Function 3) and the P18_1 to RIIC3_SCL (Function 3).


```
const ioport_pin_cfg_t g_bsp_pin_cfg_data[] =
{
    {.pin      = BSP_IO_PORT_18_PIN_00,
     .pin_cfg = ((uint32_t) IOPORT_CFG_PERIPHERAL_PIN |
                 (uint32_t) IOPORT_PERIPHERAL_MODE3)},
    {.pin      = BSP_IO_PORT_18_PIN_01,
     .pin_cfg = ((uint32_t) IOPORT_CFG_PERIPHERAL_PIN |
                 (uint32_t) IOPORT_PERIPHERAL_MODE3)},
};
```

7. Viewing Temperature and Humidity Data


Use the following procedure to view temperature and humidity data in real time.

In this chapter, HS300X is used as example figures, but HS400X works the same way.


After executing debugging, select [Window] → [Show View] → [Expressions] to open the [Expressions] tabbed page.




Click on [Add new expression] on the [Expressions] tabbed page and add "gs_hs400x_data".



Right-click on the added variable and select [Enable Real-time Refresh].



Start debugging, and the temperature and humidity values will be updated in real time.



Revision History

Rev.	Date	Description	
		Page	Summary
1.00	June 30, 2022	-	First Release
1.10	August 30, 2022	-	Add : RZ items
1.11	March 3, 2023	-	Updated: Environments for RL78
1.12	March 29, 2023	-	Updated: Environments for RA, RX, RL78, RZ Updated: Main Processing Flow of Sample Software Updated: Guide for Changing the Target Device
1.13	September 7, 2023	-	Updated: Guide for Changing the Target Device Deleted: RE01 items
1.14	April 9, 2024	-	Add : Environments for RA0E1 Updated : I2C Driver Settings of RA Family Updated : Guide for Changing the Target Device of RA Sample Project

General Precautions in the Handling of Microprocessing Unit and Microcontroller Unit Products

The following usage notes are applicable to all Microprocessing unit and Microcontroller unit products from Renesas. For detailed usage notes on the products covered by this document, refer to the relevant sections of the document as well as any technical updates that have been issued for the products.

1. Precaution against Electrostatic Discharge (ESD)

A strong electrical field, when exposed to a CMOS device, can cause destruction of the gate oxide and ultimately degrade the device operation. Steps must be taken to stop the generation of static electricity as much as possible, and quickly dissipate it when it occurs. Environmental control must be adequate. When it is dry, a humidifier should be used. This is recommended to avoid using insulators that can easily build up static electricity. Semiconductor devices must be stored and transported in an anti-static container, static shielding bag or conductive material. All test and measurement tools including work benches and floors must be grounded. The operator must also be grounded using a wrist strap. Semiconductor devices must not be touched with bare hands. Similar precautions must be taken for printed circuit boards with mounted semiconductor devices.

2. Processing at power-on

The state of the product is undefined at the time when power is supplied. The states of internal circuits in the LSI are indeterminate and the states of register settings and pins are undefined at the time when power is supplied. In a finished product where the reset signal is applied to the external reset pin, the states of pins are not guaranteed from the time when power is supplied until the reset process is completed. In a similar way, the states of pins in a product that is reset by an on-chip power-on reset function are not guaranteed from the time when power is supplied until the power reaches the level at which resetting is specified.

3. Input of signal during power-off state

Do not input signals or an I/O pull-up power supply while the device is powered off. The current injection that results from input of such a signal or I/O pull-up power supply may cause malfunction and the abnormal current that passes in the device at this time may cause degradation of internal elements. Follow the guideline for input signal during power-off state as described in your product documentation.

4. Handling of unused pins

Handle unused pins in accordance with the directions given under handling of unused pins in the manual. The input pins of CMOS products are generally in the high-impedance state. In operation with an unused pin in the open-circuit state, extra electromagnetic noise is induced in the vicinity of the LSI, an associated shoot-through current flows internally, and malfunctions occur due to the false recognition of the pin state as an input signal become possible.

5. Clock signals

After applying a reset, only release the reset line after the operating clock signal becomes stable. When switching the clock signal during program execution, wait until the target clock signal is stabilized. When the clock signal is generated with an external resonator or from an external oscillator during a reset, ensure that the reset line is only released after full stabilization of the clock signal. Additionally, when switching to a clock signal produced with an external resonator or by an external oscillator while program execution is in progress, wait until the target clock signal is stable.

6. Voltage application waveform at input pin

Waveform distortion due to input noise or a reflected wave may cause malfunction. If the input of the CMOS device stays in the area between V_{IL} (Max.) and V_{IH} (Min.) due to noise, for example, the device may malfunction. Take care to prevent chattering noise from entering the device when the input level is fixed, and also in the transition period when the input level passes through the area between V_{IL} (Max.) and V_{IH} (Min.).

7. Prohibition of access to reserved addresses

Access to reserved addresses is prohibited. The reserved addresses are provided for possible future expansion of functions. Do not access these addresses as the correct operation of the LSI is not guaranteed.

8. Differences between products

Before changing from one product to another, for example to a product with a different part number, confirm that the change will not lead to problems. The characteristics of a microprocessing unit or microcontroller unit products in the same group but having a different part number might differ in terms of internal memory capacity, layout pattern, and other factors, which can affect the ranges of electrical characteristics, such as characteristic values, operating margins, immunity to noise, and amount of radiated noise. When changing to a product with a different part number, implement a system-evaluation test for the given product.

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
4. You shall be responsible for determining what licenses are required from any third parties, and obtaining such licenses for the lawful import, export, manufacture, sales, utilization, distribution or other disposal of any products incorporating Renesas Electronics products, if required.
5. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
6. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.
 - "Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.
 - "High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.
7. Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
7. No semiconductor product is absolutely secure. Notwithstanding any security measures or features that may be implemented in Renesas Electronics hardware or software products, Renesas Electronics shall have absolutely no liability arising out of any vulnerability or security breach, including but not limited to any unauthorized access to or use of a Renesas Electronics product or a system that uses a Renesas Electronics product. RENESAS ELECTRONICS DOES NOT WARRANT OR GUARANTEE THAT RENESAS ELECTRONICS PRODUCTS, OR ANY SYSTEMS CREATED USING RENESAS ELECTRONICS PRODUCTS WILL BE INVULNERABLE OR FREE FROM CORRUPTION, ATTACK, VIRUSES, INTERFERENCE, HACKING, DATA LOSS OR THEFT, OR OTHER SECURITY INTRUSION ("Vulnerability Issues"). RENESAS ELECTRONICS DISCLAIMS ANY AND ALL RESPONSIBILITY OR LIABILITY ARISING FROM OR RELATED TO ANY VULNERABILITY ISSUES. FURTHERMORE, TO THE EXTENT PERMITTED BY APPLICABLE LAW, RENESAS ELECTRONICS DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT AND ANY RELATED OR ACCOMPANYING SOFTWARE OR HARDWARE, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.
8. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
9. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
11. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
12. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
13. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
14. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

(Rev.5.0-1 October 2020)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

Contact information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/.